



# 3RR SERIES Removable Shock Rack Transport



- Meets or Exceeds MIL-STD 810G
- Standard payload range 40 to 150 lbs.
- Optional extended payload range 160 to 300 lbs.
- Standard 19" Rack width per ANSI/EIA-310-C
- Standard Rack depth 24" rail to rail
- Square hole rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts
- 2" front lid, and 5" rear lid with edge casters standard, other options available
- SKB's Rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers cases
- Black powder coated stainless steel hardware (standard) which is recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic pressure relief valve (standard)
- Lid hangars (standard)
- Case coupling straps (standard)



## Case Specifications

All Standard depths - front to rear rail: 24"

PART#	LID DEPTH		RACK UNITS	RACK HEIGHT
	FRONT	REAR		
3RR-3U24-25B	2" / 5.1 cm	5" / 12.7 cm	3 space	5.5" / 14 cm
3RR-4U24-25B	2" / 5.1 cm	5" / 12.7 cm	4 space	7" / 17.8 cm
3RR-5U24-25B	2" / 5.1 cm	5" / 12.7 cm	5 space	8.75" / 22.2 cm
3RR-7U24-25B	2" / 5.1 cm	5" / 12.7 cm	7 space	12.25" / 31.1 cm
3RR-9U24-25B	2" / 5.1 cm	5" / 12.7 cm	9 space	15.75" / 40 cm
3RR-11U24-25B	2" / 5.1 cm	5" / 12.7 cm	11 space	19.25" / 48.9 cm
3RR-14U24-25B	2" / 5.1 cm	5" / 12.7 cm	14 space	24.5" / 62.2 cm



[www.skbcases.com](http://www.skbcases.com)

MUSIC PRODUCTS 800.410.2024

SPORTS PRODUCTS 800.654.5992

INDUSTRIAL PRODUCTS 800.783.0087